



**18V**  
Lithium-ion

**EXPAND YOUR  
LITHIUM LINE UP**

**Battery & Charger Time Reference Chart (in Minutes)**

	DC18RC / DC18RA	DC18SF	DC18SD	DC18SE (Automotive)
BL1840 4.0Ah	36min. Fast Charging	90min. 180min.	1 to 2 batteries 3 to 4 batteries	90min.
BL1830 3.0Ah	22min. Fast Charging	60min. 120min.	1 to 2 batteries 3 to 4 batteries	60min.
BL1815N 1.5Ah	15min. Fast Charging	30min. 60min.	1 to 2 batteries 3 to 4 batteries	30min.

**Dust cup set**

For Model DHR263  
Use with Grip base set  
Part No. 194582-3



Part No.

195173-3

**Cordless Combination Hammer**

**DHR264 / DHR263** 26mm (1") Adapted for SDS-PLUS bits

442

- Variable Speed
- Reversing
- SDS-PLUS Shank
- Torque Limiter
- Dust Collecting
- Built-in Job Light
- Carrying Case

	DHR264	DHR263
<b>Capacity</b>	Concrete : 26mm (1") Steel : 13mm (1/2") Wood : 32mm (1-1/4")	Concrete : 26mm (1") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
<b>Impacts per minute (ipm)</b>	0-5,000	0-5,000
<b>No load speed (rpm)</b>	0-1,250	0-1,250
<b>Dimensions (L x W x H)</b>	374x116x232mm (14-3/4"x4-9/16"x9-1/8")	350x116x232mm (13-3/4"x4-9/16"x9-1/8")
<b>Net weight*</b>	4.7kg (10.3lbs)	4.6kg (10.1lbs)

**Standard Equipment :**

Fast Charger, Battery Cartridge, Depth Gauge, Side Grip, Quick Change Drill Chuck (DHR264 only), (Tool does not come with bit.)

\*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-BC



**Cordless Combination Hammer**

**DHR264 / DHR263** 26mm (1")

Quick change chuck

Satisfy Professional's Needs



Adapted for  
SDS-PLUS bits



**18V + 18V → 36V**



**Powered by two 18V Li-ion  
batteries in series**

Photo : DHR263  
Tool does not come with bit.


# Outstanding Performance and Compact Design

Photo : DHR263  
Tool does not come with bit.

Anti-slip soft grip  
Reverse switch operable by one hand

 One touch slide chuck adapted for SDS-PLUS bit

40 different bit-angle settings



Elastomer for front guard



**Dust cup (option)**  
can be attached using adapter. (for DHR263 only)

Photo : DHR263  
Tool does not come with bit.



**18V + 18V → 36V**

## Powered by two 18V Li-ion batteries in series

Two 18V Li-ion batteries can be directly installed on the machine to supply energy to the powerful 36V DC motor drive system.  
The compatible batteries are: 1.5Ah BL1815N, 3.0Ah BL1830, 4.0Ah BL1840.



### Vibration absorbing handle provides comfortable operation.

- ergonomically designed to:
- give maximum power thrust.
  - provide a sure and comfortable grip.



### Quick change chuck

(for DHR264 only)



### 3 mode operation

- Rotation only
- Rotation + Hammering
- Hammering only

### Battery capacity warning lamp



- When remaining battery capacity decreases below a certain limit, the motor automatically stops and solid red light reminds you to replace battery.
- One warning lamp for each individual battery

### LED job light

- with preglow and afterglow functions
- On pulling switch trigger, the light automatically turns on before motor starts turning.
  - keeps on illuminating about 12-13 sec. after trigger release.

### Extreme Protection Technology

For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.

